



Experience style
and performance
in a single unit

elite

AN ELEGANT PERFORMER



In-built
Battery
Enclosure



Easily
Movable



Fast Charge
Technology



In-built
Bypass
Switch



LCD
Display



TECHNICAL SPECIFICATIONS

ELITE SINEWAVE UPS		
Product	ELITE 1500 LCD 12V SW	ELITE 1500 12V SW LED
Input Voltage	Inverter Mode: 100V - 300V UPS Mode: 180V - 260V	
Output Voltage	Mains Mode: Same as Input / UPS Mode: 210V \pm 10%	
Output Frequency	UPS Mode: 50HZ \pm 0.1HZ	
Switching	Automatic (from Mains to UPS and from UPS to Mains)	
Output Waveform	Mains Mode: Same as Input / UPS Mode: Pure Sinewave	
Batt. Charging Current	Constant Charging approx. 10% of the rated Battery Current in AH	
Charger	Power Factor Controlled Boost Technology	
Efficiency	> 80%	
UPS Overload	110%	
UPS Short Circuit	300%	
UPS Transfer Time	\leq 15msec.	
Browns Out Mains Vol.	100 \pm 40V	
Technology	Micro Computer Based intelligent Control Design	
Auto Reset Feature	Yes	
Operating Temp.	0°C ~ 45°C	

NOTE: *Power Factor may vary depending upon the load. * Because of a policy of continuous product improvement, specifications are subject to change without notice.



**Strong
Wheelbase**



**UPS and
Inverter mode**



**Quick Battery
Charging**



**Foolproof
Safety**



**Generator
Compatible**



**Protection from
Short Circuit**



Mixer-Grinder



Fans/Lights



LED TV



Laptop



Wi-Fi Router

3 YEARS ONSITE WARRANTY

Unmatched All-India Service Network

CALL/WHATSAPP: 7283838383 | www.microtek.in